



MINI Countryman JCW ALL4, type U25, 11/2023=>

2.0l Turbo 221kW (B48A, with GPF)

SECONDARY-CAT-BACK-SYSTEM EC APPROVED

WEIGHT

-11,8 KG

RACING-GPF-BACK-SYSTEM:

WEIGHT

-11,3 KG

Available for order now, delivery in calendar week 32



MINI Countryman JCW ALL4, type U25, 11/2023=>

2.0l Turbo 221kW (B48A, with GPF)

ABOUT

Secondary-Cat-Back-System L/R:

750024 0300 + 750024 1500 + tail pipe set! No vehicle modifications required!

Racing-GPF-Back-System L/R:

750024 1000 +750024 1300 + 750024 1500 + tail pipe set! No vehicle modifications required!

The use of racing products and products that do not have EC approval is not permitted on public roads.

When installing REMUS sports silencers, cat-back systems and cat replacement pipes designed for use on closed roads, it is advantageous to carry out ECU remapping in order to exploit the optimum performance of the exhaust system and prevent the engine control light from lighting up.



MINI Countryman JCW ALL4, type U25, 11/2023=>

2.0l Turbo 221kW (B48A, with GPF)

7500241000

RACING cat-replacement tube (secondary-cat-replacement tube)

Connection to front parts at the manufacturer connection point

Installation/fitting at the serial mounting points.

Only mountable in combination with 750024 1300 or 750024 0300 + 750024 1500 + tail pipe set

Original tube Ø 70 mm - REMUS tube Ø 76 mm

No EC type approval

150,-

750024 1300

RACING center-section replacement tube with spherical connection

Connection to front parts at the manufacturer connection point

Installation/fitting at the serial mounting points.

Including mounting material

Only mountable in combination with 750024 1500 + tail pipe set

Original tube \emptyset 70 mm - REMUS tube \emptyset 76 mm

No EC type approval

192,-

750024 0300

Resonated center section (absorption principle)

Connection to front parts at the manufacturer connection point

Installation/fitting at the serial mounting points

Only mountable in combination with 750024 1500 + tail pipe set

Including mounting material

Original tube Ø 70 mm - REMUS tube Ø 76 mm

incl. EC type approval

272.-

750024 1500

Sport exhaust centered (absorption principle) for L/R system

2 outer outlet tubes with integrated valves 2 inner outlet tubes without valves Installation/fitting at the serial mounting points

Only mountable in combination with 750024 0300 or 750024 1300 + tail pipe set Including mounting material

The supplied 2 actuators activate the valves via the vehicle onboard electronics.

incl. EC type approval

1.621,-



DESIGN

MAKES THE DIFFERENCE



0046 83CR

Stainless steel tail pipe set

4 tail pipes Ø 84 mm Street Race, straight, carbon insert, with adjustable spherical clamp connection

452,-



0046 83CTSR

Carbon tail pipe set

4 tail pipes Ø 84 mm angled, Titanium internals, with adjustable spherical clamp connection

896.-



0046 83CSR

Stainless steel tail pipe set

4 tail pipes Ø 84 mm Carbon Race, angled, carbon ring, with adjustable spherical clamp connection

468,-



0046 55SR

Stainless steel tail pipe set

4 tail pipes Ø 84 mm angled, rolled edge, chromed, with adjustable spherical clamp connection

372.-



0046 83CBR

Stainless steel tail pipe set

4 tail pipes Ø 84 mm Street Race Black Chrome, straight, carbon insert, with adjustable spherical clamp connection

508,-



SOUND

FIRST CLASS QUALITY DESIGNED & BUILT IN EUROPE | AUSTRIA

www.remus.eu











in remus.sportexhaust

REMUS Innovation GmbH Ruhmannstraße 11 A-8570 Voitsberg